

Type	Dimensions (mm)							$\alpha \approx$	Load Ratings		Weight =kg
	d	D	B	C	dk	r1s min	r2s min		Dynamic	Static	
GE20ES-2RS	20	35	16	12	29	0.6	0.3	9	30	146	0.061
GE25ES-2RS	25	42	20	16	35.5	0.6	0.6	7	48	240	0.11
GE30ES-2RS	30	47	22	18	40.7	0.6	0.6	6	62	310	0.14
GE35ES-2RS	35	55	25	20	47	0.6	1	6	80	400	0.22
GE40ES-2RS	40	62	28	22	53	0.6	1	7	100	500	0.3
GE45ES-2RS	45	68	32	25	60	0.6	1	7	127	640	0.4
GE50ES-2RS	50	75	35	28	66	0.6	1	6	156	780	0.54
GE60ES-2RS	60	90	44	36	80	1	1	6	245	1220	1
GE70ES-2RS	70	105	49	40	92	1	1	6	315	1560	1.5
GE80ES-2RS	80	120	55	45	105	1	1	6	400	2000	2.2
GE90ES-2RS	90	130	60	50	115	1	1	5	490	2450	2.7
GE100ES-	100	150	70	55	130	1	1	7	610	3050	4.3
GE110ES-	110	160	70	55	140	1	1	6	655	3250	4.7
GE120ES-	120	180	85	70	160	1	1	6	950	4750	8
GE140ES-	140	210	90	70	180	1	1	7	1080	5400	11